


Arc

AS-10

Passive subwoofer for fixed installations, 2 × 6.5", 300 W, 120 dB SPL max., 40 Hz – 500 Hz, 440 × 250 × 380 mm



Arc AS-10

The AS-10 is a very compact, passive subwoofer for fixed installations. It is the optimum addition to the compact fullrange speakers of the Arc, Linea and Integrato series. It impresses with its precise reproduction of bass frequencies and high-performance capacity despite its small dimensions.



Main features

- 2 × 6.5" long excursion driver
- 300 W nominal power rating
- Vented enclosure with non-turbulent port design (Fohhn NTP)
- SPL max.: 120 dB
- Connections: 2 × 4-pin terminal
- High-quality wooden enclosure (multiplex birch)
- Available in RAL Classic, NCS or Pantone colors on request
- Optionally available with weatherproof PU coating
- Various mounting options
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Special colors
optional



Ball impact
resistant

For detailed information about all Fohhn technologies, color options and connections, please visit www.fohhn.com/en/technologies

Technical data

Electroacoustic features	
acoustic design	vented design
power rating (nominal)	300 watts
components	2 × 6.5" long excursion, neodymium
maximum SPL	120 dB
frequency range	40 Hz – 500 Hz
nominal impedance	4 ohms

Physical features	
enclosure	multiplex birch plywood
connectors	2 x 4-pin terminal
dimensions (w × h × d)	440 × 250 × 380 mm
weight	9 kg
standard colours	textured paint, black
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	6 × M8 thread

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

power rating (nominal/program): according to IEC-60268-5 (long term/short term)
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset
weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

