

X Series

XS-22 passive

Passive subwoofer for mobile applications, 12", 500 W, 127 dB
SPL max., 38 Hz – 500 Hz, 52 × 42 × 43 cm



X Series XS-22 passive

The XS-22 passive is a powerful 12" subwoofer. It is characterized by precise low-frequency reproduction, a high power rating and versatility.



Main features

- 12" long excursion driver
- Power rating: 500 W
- SPL max.: 127 dB
- Connections: 4 × Speakon
- High-quality wood enclosure (multiplex birch plywood)
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Lightweight, only about 21 kg
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Special colors
optional

Technical data

Electroacoustic features	
acoustic design	vented design, NTP (Non-Turbulent Portdesign)
power rating (nominal)	500 watts
components	1 × 12" long excursion
maximum SPL	127 dB
frequency range	38 Hz – 500 Hz
nominal impedance	4 ohms

Physical features	
enclosure	multiplex birch plywood
connectors	4 × NL4 Neutrik Speakon
dimensions (w × h × d)	52 × 42 × 43 cm
thread plate for distance piece	M20
weight	21 kg
standard colours	black, textured paint
handles	2 corner handles
transport wheels	no
front design	acoustically transparent foam in enclosure colour
protection grille	steel grille, ball impact resistant, powder-coated

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

power rating (nominal/program): according to IEC-60268-5 (long term/short term)
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
weight: net weight without optional equipment

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

