


# X Series

## XT-33

Passive fullrange speaker for mobile applications, 12" / 1", 500 W, 130 dB SPL max., approx. 380 × 590 × 390 mm



# X Series XT-33

The XT-33 is a powerful passive loudspeaker for mobile use. Like all tops in the X series, it delivers first-class sound as a fullrange speaker, stage monitor, nearfill or in a system with Fohhn subwoofers. The sturdy enclosure, made of multiplex birch plywood with durable paintwork, is designed for tough days on the road.



## Main features

- Equipped with: 12" / 1"
- Electronic high frequency protection
- Nominal power rating: 500 watts
- Nominal impedance: 8 ohms
- SPL max.: 130 dB
- Dispersion: 90° × 60° (H × V)
- Connections: 4 × Speakon
- Built-in flange mount and safety eyebolt
- Lightweight, only 19 kg
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Versatile accessories for mobile use
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Black

Equipped with the following Fohhn technologies



Special colors  
optional

# Technical data

Electroacoustic features	
acoustic design	passive loudspeaker, 2-ways, rotatable Constant Directivity Horn
power rating (nominal)	500 watts
power rating (peak)	900 watts
components	12" / 1" CD fully neodymium
maximum SPL	130 dB
frequency range	55 Hz – 20 kHz
nominal impedance	8 ohms
nominal dispersion (h × v)	90° × 60°

Physical features	
enclosure	multiplex birch plywood
connectors	4 × NL4 Neutrik Speakon
dimensions (w × h × d)	approx. 380 × 590 × 390 mm
angle for monitor set-up	55°
speaker stand pole	integrated, Ø 36 mm
weight	approx. 19 kg
standard colours	textured paint, black
handles	2 edge handles
EN 54-24	0
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	mounting threads for U-bracket, safety-eyelet on the back

Optional features	
optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

CAAD simulation data	
simulation data	Fohhn Designer

power rating (nominal/program): according to IEC-60268-5 (long term/short term)  
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset  
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset  
weight: net weight without optional equipment  
nominal dispersion: -6 dB compared to the main dispersion axis

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

